



## Plastic part circle Impact Sprinkler, 3/4" male

Application: General agriculture part circle

- Operating pressure 2.5 - 4.5 bar
- 30 degree main nozzle, 11 degree bottom nozzle
- Integrated vane straighteners
- High quality plastic - resistant to corrosion and radiation
- Brass nozzles (also available with plastic nozzles)
- Two Year Warranty



## Performance Table - W8036PC

### Dual Nozzle

Nozzle mm	P Bar	Q m3/h	Diameter m
4.0 x 2.4	3.0	1.44	26
	3.5	1.56	28
	4.0	1.66	28
4.4x 2.4	3.0	1.66	28
	3.5	1.79	28
	4.0	1.91	28
4.8 x 2.4	3.0	1.93	30
	3.5	2.08	30
	4.0	2.22	32
4.8 x 3.2	3.0	2.24	27
	3.5	2.40	28
	4.0	2.56	28
5.2 x 3.2	3.0	2.48	28
	3.5	2.67	29
	4.0	2.84	29

### Single Nozzle

Nozzle mm	P Bar	Q m3/h	Diameter m
4.0	3.0	1.03	26
	3.5	1.13	27
	4.0	1.21	27
4.4	3.0	1.24	27
	3.5	1.36	28
	4.0	1.45	28
4.8	3.0	1.50	27
	3.5	1.63	28
	4.0	1.72	28
5.2	3.0	1.77	28
	3.5	1.93	29
	4.0	2.05	29
5.6	3.0	1.78	28
	3.5	2.23	29
	4.0	2.36	30