

Hydrant Valves

Hydrant valves for attaching to a main water line. Made from a high grade aluminium alloy to resist groundwater corrosion. Four different sizes are available in one inch increments from 3" (75 mm) to 6" (150 mm), all with BSP thread. Available in cast iron and brass to suit mineral rich water, and Southern Cross compatible. Spare parts available including hydrant valve body, valve cap, hyrel seal, locknut, santoprene, washer, pin, spindle nut, threaded spindle.

Complete Hydrant Valves

Product Code	Description
HVC080	3" BSP (80 mm) Complete Hydrant Valve
HVC100	4" BSP (100 mm) Complete Hydrant Valve
HVC125	4" BSP (100 mm) Complete Hydrant Valve
HVC125CI	5" BSP (125 mm) Complete Hydrant Valve With Cast Iron Body
HVC150	6" BSP (150 mm) Complete Hydrant Valve



HYDRANT VALVES

Hydrant Flow Rate

4" Valve	300 GPM – 1.0 PSI loss
	400 GPM – 3.0 PSI loss
	450 GPM – 4.0 PSI loss

Hydrant Take Off Elbows

Available in four different sizes in one inch increments from 3" (75 mm) to 6" (150 mm), all with BSP thread. Case and turn key are a high grade alloy. Secure mounting with three and two bronze lug attachments depending on size. Adaptable to other systems, such as Southern Cross, Harrison and Homershom. All hydrant take off elbows are available in an extended form that adds 40 mm to the length between the inlet base and outlet aperture.

Hydrant Take off Elbows

Product Code	Description
HTOC080	3" BSP (80 mm) Complete Hydrant Take Off Elbow
HTOC100	4" BSP (100 mm) Complete Hydrant Take Off Elbow
HTOC125	5" BSP (125 mm) Complete Hydrant Take Off Elbow
HTOC150	6" BSP (150 mm) Complete Hydrant Take Off Elbow



HYDRANT TAKE OFF
ELBOWS